

MICROPOROUS MEMBRANE MATERIALS

膜过滤器系统

New Generation Membrane Separation Refined Filtration System

型号 Model:JY-T32A

工作压力 Working Pressure: 0.2~0.3 Mpa

流量 Flow Rate(According to oil quality): 50L/min (max)

滤芯精度 Precision:5~25µm

滤芯材质 Filtering material: Polymer membrane materials

电压 Voltage: DC12V/24V/220V 接口尺寸 Flange Mouth: DN25

适用油品 Apply to oil: Diesel fuel, Aviation fuel 尺寸 Measurement:680×480×880mm



Filtration, Purification & Separation Solutions

JY-T32A

油品净化过滤器

Diesel Fuel Filtration







Filter Technology Solutions Partner

主要特点/FEATURES

Can effectively intercept and separate impurities, colloid, water and micro particles in oilThe oil becomes clear and transparent after filtration, and the cleanliness level is greatly improved, effectively extending the service life of mechanical equipment

Comply with the national environmental protection regulations, no pollution consumables, no diesel consumption, no need to clear sand and slag

The polymer membrane filter elements can be used repeatedly after blowing,

save the cost of consumables

The equipment operation is simple, and there is a professional after-sales team tracking service, let you have no worries

Be suitable for gas station/ construction machinery/ and other places need oil filtration

Jingyuan has a one-stop product development and production system from the development of membrane materials to finished products To provide users with satisfactory dedicated filters and their systems





Gas Station Application.



MICROPOROUS MEMBRANE MATERIALS (膜型号及规格)

Membrane filter order models	Nominal Pore Size
J22-330 L/H	0.5~15 μ m
J22-400 L/H	
J30-970 L/H	0.5~25 µ m
J30-980 L/H	







晶元濾膜(沈陽)有限公司 SHENYANG JINGYUAN MEMBRANE SYSTEMS CO.,LTD. 工厂地址: 辽宁省铁岭懿路工业园区桃李沟路19号 电话: 024-78715999 139 0405 2025